



Based on Cover, the first one is Back pin header.

公差等级/General Tolerances(mm)		公差等级/General Tolerances(mm)										公差等级/General Tolerances(mm)	
0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	0.1/1.0
3	~	~	~	~	~	~	~	~	~	~	~	~	±2
6	~	~	~	~	~	~	~	~	~	~	~	~	±2
10	~	~	~	~	~	~	~	~	~	~	~	~	±2
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±1.05	±1.15	±1.60	±2.20	±2.50	±2

ITEM	NAME OF PART	MATERIAL	NOTES
6	Spring	Stainless steel	/
5	Back pin header	Copper	/
4	Front pin header	Copper	Sn Plated
3	Cover	PA66	UL94V-0
2	Center housing	PA66	UL94V-0
1	End housing	PA66	UL94V-0

UL 标准/UL Standard:	B	C	D
额定电压/额定电压(V)/Current(A)	600/40	600/40	600/5
IEC 标准/IEC Standard:			
过电压类别/Overvoltage Category/污秽等级	III/3	III/2	II/2
污染等级/Pollution Degree			
额定电压/额定电压(V)/Current(A)	630/41	1000/41	1000/41
额定冲击电压(KV)/Rote Impulse Voltage(KV)	8	8	8
额定容量(额定值)/Wire Range(rigid and flexible)(mm²/AMC)	0.2-6/24~8		
间距/Pitch(mm)/线数/极数/Poles	7.5/N=02~16P		
剥线长度/Stripping length(mm)	14-15		
使用温度范围/Operating temperature(°C)	-40~+105		
符合RoHS环保要求/Conform to RoHS	Yes		

MATERIAL: /

MAT NO.: /

STATUS: /

APPD: Li GL 2020.05.15

CHKD: MoEK 2020.05.15

DRT: BYH 2018.10.08

NAME: **DEGSON® NINGBO DEGSON ELECTRICAL CO., LTD**

DWG NO.: DG271V-7.5-DB-01

TYPE: CUSTOMER DRAWING

SCALE: 2:1

REV: T1

SHEET: 1/1