



未注公差/General tolerances (mm)													0.1/10
0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50

Note:  
The A&Z(H) in the name means: A(H) and Z(H).

ITEM	NAME OF PART	MATERIAL	NOTES
7	Nut	Copper Alloy	M2.5
6	Screw	Steel	Zn Plated
5	Pin	Copper	Sn Plated
4	Cage	Copper Alloy	Ni Plated
3	Din	PA66	UL94V-0
2	Cover	PA66	UL94V-0
1	Housing	PA66	UL94V-0

UL 标准/UL Standard:	B	C	D
额定电压/电流/Rated Voltage(V)/Current(A)	300/15	/	300/10
IEC 标准/IEC Standard:	III/3	III/2	II/2
过压类别/Overtoltage Category/污染等级/Pollution Degree	250/12	320/12	630/12
额定电压/电流/Rated Voltage(V)/Current(A)	4	4	4
额定脉冲电压(KV)/Rate Impulse Voltage(KV)	M3, 0.6/5.32		
螺丝扭矩/Torque Tightening(N·m/Lb.in)	M2.5, 0.4/3.54		
线径范围(硬线和软线)/Wire Range(rigid and flexible)(AWG/mm <sup>2</sup> )	28~12/ 0.2~2.5		
间距/Pitch(mm)/线数范围/Poles	5.08/N=02~24P		
剥线长度/Stripping length(mm)	7~8		
使用温度范围/Operating temperature(°C)	-40~+105		
符合RoHS环保要求/Conform to RoHS	Yes		
标准颜色编号/Standard color number: PANTONE / RAL	/		

<b>DEGSON</b>		MATERIAL:	SURFACE/COLOR:
APPD: 兰春华	2022.11.17	MAT NO./REV: -	MAT STATUS: 批量
CHKD: 龚耀志	2022.11.17	NAME	
DRFT: 方哲盛	2022.11.17	2EDG-DKM-5.08-XXP-1Y-00A&Z(H)	
00	REV	ECN	DESCRIPTION
方哲盛	2022.11.17		
200019601	DRAWING NO.	CUSTOMER DRAWING	DRAWING STATUS
A4	TYPE	已发布	SCALE
1/1			SHEET

Transfer or duplication of this document as well as the utilization or communication of its contents are prohibited unless authorized in writing by the copyright holder. All rights reserved for patent. 除专利等明确标注外，其他内容均受版权保护。未经许可，不得复制或传播。 侵权必究。