



0	>0	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	0.170
-	-	-	-	-	-	-	-	-	-	-	-	-	>500
3	6	10	18	30	50	80	120	180	250	315	400	500	
±0.12	±0.18	±0.22	±0.28	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.30	±2.50

4	Pin	Copper alloy	Sn plated
3	Mount	Stainless Steel	/
2	Pin header	Copper	Au Plated Area
1	Housing	PA66+GF	UL94V-0
ITEM	NAME OF PART	MATERIAL	NOTES

UL 标准/UL Standard:	B	C	D
额定电压/电压/Rated Voltage(V)/Current(A)	300/14.5	/	300/10
IEC 标准/IEC Standard:			
基本类别/Over-voltage Category / 污染等级/Pollution Degree	III/3	III/2	II/2
额定电压/电压/Rated Voltage(V)/Current(A)	160/16	250/16	320/16
额定脉冲电压(RV)/Rate Impulse Voltage(KV)		4	
间距(Pitch)(mm)/间距(Pitch)(mm)		5.0(N-02-14P)	
使用温度范围/Operating temperature(°C)		-40~+105	
符合RoHS环保要求/Conform to RoHS		Yes	

DRAGON

APPRO. 批准	2024.09.02	NAME	
CHKD. 审核	2024.09.02	MATERIAL	REFERENCE COLOR:
DRW. 制图	2024.09.02	MAT. NO./REV.	/
DATE	2024.09.02	MAT STATUS:	
REV	REV	DESCRIPTION	
REV	REV	DESCRIPTION	

DRAWING NO. 200177180
 TYPE CUSTOMER DRAWING
 DRAWING STATUS 2:1
 SCALE 2:1
 SHEET 1/1

9EDGRC-5, 0-XXP-1Y-100Z (H)