



未注公差/General tolerances (mm)												0.05/10			
0 ~ 3	>3 ~ 6	>6 ~ 10	>10 ~ 18	>18 ~ 30	>30 ~ 50	>50 ~ 80	>80 ~ 120	>120 ~ 180	>180 ~ 250	>250 ~ 315	>315 ~ 400	>400 ~ 500	>500	0.05/10	±1°
±0.08	±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20		

UL 标准/UL Standard:	B	C	D
额定电压/电流/Rated Voltage(V)/Current(A)	300/30	300/30	/
IEC 标准/IEC Standard:			
过压类别/Over voltage Category/污染等级/Pollution Degree	III/3	III/2	II/2
额定电压/电流/Rated Voltage(V)/Current(A)	500/30	/	/
额定脉冲电压(KV)/Rate Impulse Voltage(KV)	6	/	/
螺丝扭矩/Torque Tightening(N·m/Lb.in)	M4. 1.5~1.8/13.28~15.94		
线径范围(硬线和软线)/Wire Range(rigid and flexible)(AWG/mm²)	24~10 /0.2~6.0 最大裸线: 8AWG/10mm²		
间距/Pitch(mm)/线数范围/Poles	8.2/N=01P		
剥线长度/Stripping length(mm)	10~11		
环境温度(运行)/Ambient temperature (operation)(°C)	-60~+105(最高短期工作温度, 电气特性相对温度。)		
符合RoHS环保要求/Conform to RoHS	Yes		

ITEM	NAME OF PART	MATERIAL	NOTES
6	Switch	PA66+Copper Alloy	UL94 V-0+Sn Plated
5	Current_Carrier_Right	Copper Alloy	Sn Plated
4	Current_Carrier_Left	Copper Alloy	Sn Plated
3	Screw	Brass	M4 Ni Plated
2	Cage	Brass	Ni Plated
1	Housing	PA66	UL94 V-0

		MATERIAL:		SURFACE/COLOR:	
APPD: PENG M 2024.08.27		MAT NO./REV: 1109000025-1 / 00.01		MAT STATUS: 小批量	
CHKD: GAO WG 2024.08.27		NAME			
DRFT: LIU Y 2024.08.27		DHVME6-01P-11-00Z (H)			
DRAWING NO. 200256830	TYPE CUSTOMER DRAWING	DRAWING STATUS 已发布	SCALE 1:1	SHEET 1/1	

REV	ECN	DESCRIPTION	DRFT	DATE
05		Redimension 1 feature .	LIU Y	2024.08.27

Transfer or duplication of this document as well as the utilization or communication of its content are prohibited unless authorized in writing by Degson. All rights reserved for patent. 除专利号明确标注外, 其他内容均受知识产权保护。未经授权, 禁止复制或传播。如有侵权, 请联系 Degson 公司。Degson 保留所有权利。